

NYLON CABLE TIES

COFIL®

**NYLON
100%**

Polyamida 6.6

UL 94V-2



+85° C

-40° C

**HIGH
QUALITY
RoHS**



The design of the housing guarantees high tightening torque

The strong inner teeth prevent slippage

Smooth edges

The inclined band-end makes assembly easy

Manufactured from high-strength PA 6.6

Band-width	Strength (KG) Standard MIL-S-23190	Temperature range	Installation temperature	Melting point	Limiting oxygen index	Smoke corro	Dielectric strength	Material
2,4	8	-40°C a + 85°C	-10°C a + 60°C	+ 256°C	27%	5%	50.000 Volts / mm.	PA 6.6
2,5	8,1	-40°C a + 85°C	-10°C a + 60°C	+ 256°C	27%	5%	50.000 Volts / mm.	PA 6.6
2,8	14	-40°C a + 85°C	-10°C a + 60°C	+ 256°C	27%	5%	50.000 Volts / mm.	PA 6.6
3,6	18,2	-40°C a + 85°C	-10°C a + 60°C	+ 256°C	27%	5%	50.000 Volts / mm.	PA 6.6
4,8	22,2	-40°C a + 85°C	-10°C a + 60°C	+ 256°C	27%	5%	50.000 Volts / mm.	PA 6.6
7,6	54,4	-40°C a + 85°C	-10°C a + 60°C	+ 256°C	27%	5%	50.000 Volts / mm.	PA 6.6
9	79,4	-40°C a + 85°C	-10°C a + 60°C	+ 256°C	27%	5%	50.000 Volts / mm.	PA 6.6
12,6	114	-40°C a + 85°C	-10°C a + 60°C	+ 256°C	27%	5%	50.000 Volts / mm.	PA 6.6