

Magnetic Aluminum Plugs

TMA

Specifications

- 11S aluminum hex head plug
- Operating temperature 212°F (100°C)
- Pressed in magnet
- BSPP threads standard
- FASIT 202 Fiber Gaskets

Options

- Aluminum gasket



Dimensional Detail

Model	F Port Thread		Ch	d	h1	h2	h3	Torque
TMA-14	1/4" BSPP	in.	0.75	0.20	0.28	0.39	0.24	5-7 ft. lbs
		mm	19	5	7.0	10.0	6.0	8-10 nm
TMA-38	3/8" BSPP	in.	0.87	0.31	0.28	0.39	0.28	5-7 ft. lbs
		mm	22	8	7.0	10.0	7.0	8-10 nm
TMA-12	1/2" BSPP	in.	1.06	0.39	0.31	0.39	0.28	7-11 ft. lbs
		mm	27	10	8.0	10.0	7.0	10-15 nm
TMA-34	3/4" BSPP	in.	1.34	0.51	0.31	0.39	0.28	7-11 ft. lbs
		mm	34	13	8	10	7	10-15 nm
TMA-1	1" BSPP	in.	1.57	0.51	0.31	0.55	0.28	7-11 ft. lbs
		mm	40	13	8	14	7	10-15 nm
TMA-1 1/4	1 1/4" BSPP	in.	1.97	0.39	0.39	0.59	0.59	7-11 ft. lbs
		mm	50	10	10	15	15	10-15 nm

