

## OIL FILL PLUGS

### Model TCN

#### Specifications

- Polyamide 66 hex head plug
- Operating temperature 212°F (100°C)
- FASIT 202 fiber gasket
- Fill graphic symbol standard
- BSPP or metric threads standard

#### Option Available

- Rubber gasket
- Breather hole 2-3.5 mm



## Dimensional Detail

Model	F Port Thread		Ch	D	h2	h1		Torque
TCN-14	1/4" BSPP	in	0.67	0.77	0.35	0.28	ft-lbs	3.7
		mm	17	20	9.0	7.0	NM	5
TCN-38	3/8" BSPP	in	0.71	0.87	0.39	0.30	ft-lbs	5.9
		mm	18	22	10.0	7.5	NM	8
TCN-12	1/2" BSPP	in	0.91	1.10	0.43	0.30	ft-lbs	6.6
		mm	23	28	11.0	7.5	NM	9
TCN-34	3/4" BSPP	in	1.18	1.34	0.43	0.35	ft-lbs	8.1
		mm	30	34	11	9	NM	11
TCN-1	1" BSPP	in	1.38	1.65	0.47	0.41	ft-lbs	14.8
		mm	35	42	12	10.5	NM	20
TCN-1-NPT	1" NPT	in	1.65	2.01	0.53	0.47	ft-lbs	
		mm	42	51	13.5	12	NM	
TCN-114	1 1/4" BSPP	in	1.97	2.28	0.63	0.39	ft-lbs	
		mm	50	58	16	10	NM	
TCN-112	1 1/2" BSPP	in	2.52	2.91	0.63	0.47	ft-lbs	
		mm	64	74	16	12	NM	
TCN-1015	M10 X 1.5	in	0.67	0.77	0.35	0.28	ft-lbs	3.7
		mm	17	19.5	9	7	NM	5
TCN-1215	M12 X 1.5	in	0.67	0.77	0.35	0.28	ft-lbs	3.7
		mm	17	19.5	9	7	NM	5
TCN-1415	M14 X 1.5	in	0.67	0.77	0.35	0.28	ft-lbs	3.7
		mm	17	19.5	9	7	NM	5
TCN-1615	M16 X 1.5	in	0.71	0.83	0.39	0.30	ft-lbs	4.4
		mm	18	21	10	7.5	NM	6
TCN-1815	M18 X 1.5	in	0.83	1.02	0.39	0.30	ft-lbs	5.2
		mm	21	26	10	7.5	NM	7
TCN-2015	M20 X 1.5	in	0.94	1.10	0.39	0.31	ft-lbs	6
		mm	24	28	10	8	NM	8
TCN-2215	M22 X 1.5	in	0.94	1.10	0.43	0.31	ft-lbs	7.4
		mm	24	28	11	8	NM	10
TCN-4015	M40 X 1.5	in	1.65	2.05	0.51	0.39	ft-lbs	
		mm	42	52	13	10	NM	

