

DRIVEN BY AIR.

airlite

eco

PCL



A must have, cost-effective addition to general trade or an auto enthusiast's tool kit.

- » Manufactured from nylon filled polymer
- » Increased window size ensures clearer, easy to see readings
- » Fast Inflate and deflate
- » Textured thumb lever allows greater control and comfort in use

PCL's new airtite eco Linear Tyre Inflator handles the pressures without breaking the bank. It's customer led ergonomic design and the natural insulation of the polymer ensures user comfort during use.

The two-stage valve design ensures accuracy and longer life compared to competitors' single-stage mechanisms, where filters are used in an attempt to protect the product - this can result in over 50% reduction in product life, with filters slowing down inflation rates.

At the same time the two-stage valve - that also features on the airtite's big brother 'AIRFORCE MK4' - creates less drag, reduced friction & less movement inertia means no internal corrosion, no sticking and no skewing of accuracy.



SUITABLE FOR



CONTACT YOUR LOCAL PCL DEALER FOR MORE INFORMATION



www.pclairtechnology.com

A HORNGROUP BRAND

DRIVEN BY AIR.

airlite

eco

PCL

Manufactured from nylon filled polymer, providing natural insulation for a warm, robust feel

Cycle tests give over 250,000 inflation cycles at 100% accuracy



Piston & Seal Design - Less drag, reduced friction and less movement inertia means no internal corrosion, no sticking and no skewing of accuracy

Fast Inflate and deflate - Takes 62 seconds to fill to 3 bar


Textured thumb lever allows greater control and comfort when inflating or deflating



0.4m hose with two tyre valve connector options available

Increased window size ensures clearer, easy to see readings

Lightweight only 704 g, reduces fatigue



Two stage valve arrangement prevents user having to 'push' against full line pressure on deflate. Prevents fatigue when deflating

Product Options

Part No.	Hose Length	Tyre Valve Connection	Calibration	Maximum Inlet Pressure
LAG1H03	0.4 m	Twin Hold-on	0-140 psi / 0-9.6 bar	188 psi / 13 bar
LAG1H08	0.4 m	Euro Clip-on	0-140 psi / 0-9.6 bar	188 psi / 13 bar

Explore the Linear Tyre Inflator range

Find out which inflator is best for you; the new economy airtite eco, or the premium AIRFORCE® MK4



CONTACT YOUR LOCAL PCL DEALER FOR MORE INFORMATION



www.pclairtechnology.com

A HORNGROUP BRAND